Stainless steel insert ball bearig - inner ring extended on one side with grub screws



SB200
Spherical O.D.



CSB200
Cylindrical O.D.

2RS TYPE SEAL

H TYPE SEAL

Dimension table . Dimensions in mm

Bearing No.	Shaft Dia d (mm)	(in)	Bearing Dimensions D	Bi	Be	n	m	G	ds (mm)	Basic dynamie Load ratings (N)	Basic static Load ratings (N)	weight (kg)
SSSB 204	20		47	25	14	7.0	18.0	5.0	M6x1	9 880	6 200	0.12
SSCSB 204-12		3/4										
SSSB 205	25		52	27	15	7.5	19.5	5.5	M6x1	10 780	6 980	0.18
SSCSB 205-14		7/8										
205-15		15/16										
205-16		1										
SSSB 206	30		62	30	16	8.0	22.0	5.9	M6x1	14 970	10 040	0.26
SSCSB 206-17		1-1/16										
206-18		1-1/8										
206-19		1-3/16										
206-20		1-1/4										
SSSB 207	35		72	32	17	8.5	23.5	8.0	M8x1	19 750	13 700	0.43
SSCSB 207-20		1-1/4										
207-21		1-5/16										
207-22		1-3/8										
207-23		1-7/16										
SSSB 208	40		80	34	18	9	25.0	8.0	M8x1	22 710	15 940	0.60
SSCSB 208-24		1-1/2										
208-25		1-9/16										
SSSB 209	45		85	36	19	9.5	31	8.0	M8x1	24 360	17 710	0.80
SSCSB 209-26		1-5/8										
209-27		1-11/16										
209-28		1-3/4										
SSSB 210	50		90	38	20	10	32.6	10.0	M10x1.25	26 980	19 840	0.83
SSCSB 210-30		1-7/8										
210-31		1-15/16										
210-32		2										